

QUICK START GUIDE

For a perfect start.















Preparation I Instructions for use

Preparation

- Before applying the material, the surface must be clean and free of surface contamination.
- \bullet The surface can be sandblasted with 50/110 μm and 1.5 bar pressure.

Instructions for use

- Do not pour surplus liquid out of the container. Mix it back into a paste.
- Mix MiYO Color, MiYO Structure and Glaze Paste thoroughly with a metal free spatula before each use.
- The pastes must not come into contact with water.
- Always use a clean and dry brush.

Storage and disposal

- Store in a dry place.
- Small quantities can be deposited in household waste.



Mix thoroughly with a metal-free spatula.



Firing parameter*	
Start temperature [°C]	450
Dry time [min]	3
Closing time [min]	4
Heat rate [°C / min]	45
Vacuum start [°C]	580
End temperature [°C]	710-720
Vacuum end [°C]	710-720
Holding time [min]	1
Opening time [min]	1

^{*} The firing temperatures are standard values and may vary depending on the type of furnace.



Downloads

The Safety Data Sheet and the Quick Start Guide are available for download at:

www.jensendental.de/downloads





Webshop

24/7 you can order in our order in our webshop.

https://shop.jensendental.de/





Support

General requests: info@jensendental.de +49 7123 92260 Technical support: support@jensendental.de



Sales and Technical Support Europe:

Jensen Dental GmbH Gustav-Werner-Straße 1 72555 Metzingen, Germany 0800-8573230 | +497123-92260 info@jensendental.de www.jensendental.de | www.miyoworld.eu

Manufactured by:

ChemichI AG Landstrasse 114 9490 Vaduz, Liechtenstein info@chemichl.com www.chemichl.com

